Specifications

This controller is suitable for domestic heat pump Automatic control constant temperature

High temperature disinfection . Two fans control

Simple operation

RBYT0000-0571A005

New all in one domestic heat pump Controller

General:

This controller is designed for domestic heat pump heat pump, suitable for all in one heat pump. Single compressor control, with strongly system protection, has pass EMC industrial standard certificate. The controller with advance functions and groundbreaking applications for the HVAC market.

Features:

- 1. With touch button LED display, quick parameter setting, easy operation
- 2. Intelligent defrost control mode, more stable and energy saving,
- 3. Power off memory function
- 4、EEV control function
- 5. Working modes: Heating mode . High temperature disinfection mode
- 6. Kitchen refrigeration function
- 7、24 hour cycle Timing ON/OFF function
- 8、Five way control output: Compressor, Auxiliary heater, Fan motor...etc
- Six way sensor input: Upper water tank temperature sensor, Lower water tank temperature sensor, Climate temperature sensor...etc
- 10. Two way switch input: Compressor high pressure switch ,Compressor low pressure switch

Technical parameters:

- 1、Measuring range:-30°C~99°C
- 2、Controlling range:-30°C~99°C;
- 3、Accuracy:-30°C~50°C,±1°C±0.5dig; others, ±2°C±0.5dig
- 4. Mounting size: 119×99×25mm
- 5、 Power supply: 220±10%(VAC), 50/60Hz
- 6, Power consumption:<12W
- 7. Storage temperature:-25°C~50°C
- 8、Senor type: NTC(5K /25°C,B value 3470K; 50K /25°C,B value 3490K)
- 9. Port output capacity:

Compressor: 30A/250VAC Auxiliary heater: 30A/250VAC

Others: 5A/250VAC

10、Product list: RBYT0000-0571A005 (1pcs),LCD display



(1pcs), ,Transformer(1PCS), temp. sensor(6PCS)



Application

